



# DISQ HF



|                         |                 |                                  |                   |
|-------------------------|-----------------|----------------------------------|-------------------|
| Beamangle               | 180°            | Input current                    | 480mA             |
| CIE Flux Codes          | 46 76 95 100 93 | IP                               | IP44              |
| Colour Deviation (SDCM) | 3 sdcM          | Color                            | Wit               |
| Colour Temperature      | 3000K           | Led type                         | SMD               |
| Max. connected Load     | 22W             | Lumen Maintenance                | L80B10 bij 50.000 |
| Connected Voltage       | 220-240V        | Lumen/W                          | 135lm/W           |
| CRI                     | 80              | Luminous flux of luminaire       | 2200lm            |
| Dim                     | Nee             | Material Housing                 | Plastic           |
| Dimensions              | Ø340x100        | Material Lens/Reflector/Diffusor | Plastic           |
| Energy Efficiency Class | D               | Mounting Type                    | Ceiling           |
| Forward Voltage         | 27-36V          | PF                               | 0,9               |
| Frequency               | 50-60Hz         | Protection Class                 | I                 |
| IK                      | 07              | UGR                              | <19               |
|                         |                 | Weight                           | 0,5kg             |

Reference : 000002501

## Product Description

De Disq is een lamp die technische innovatie en tijdloos design combineert. Het heeft een geïntegreerde lichtbron achter duurzaam PVC, wat zorgt voor onzichtbare verlichting. De gesatineerde diffusor zorgt voor gelijkmatige lichtverspreiding. Met een IP44-classificatie is de Disq bestand tegen vuil en water, hierdoor is hij geschikt voor veeleisende omgevingen. De lamp heeft een kleurtemperatuur van 3000K en kan zowel aan het plafond als aan de wand worden gemonteerd, waardoor hij veelzijdig inzetbaar is in verschillende toepassingen, zoals openbare gangen, stockeruimtes en badkamers. Uitgerust met een bewegingssensor waardoor de Disq uitlicht wanneer iemand de ruimte binnenkomt. Het biedt een combinatie van functionaliteit en elegantie met hoogwaardige circulaire componenten die stuk voor stuk vervangen kunnen worden. Een eendeloos armatuur.